

SPECIFICATION

AF0807 Series 4-Ball Piston Pumps

Ratio 7:1

Stroke 6" (15.24 cm)

Material Inlet 1-1/2" NPT(F)2" NPT(M)

Material Outlet 1" NPT(F)

Air Inlet (female) 1/2" NPT(F)

Air Inlet Pressure Range psi (bar) 30 - 120 (2.1 - 8.3)

Fluid Pressure Range psi (bar) 210 - 1009 (14.5 - 69.6)

Max Cycles/Minute 70

Displacement/Cycle cu in (cm3) 77.5 (1269.9)

Cycles/gal (L) 2.9 (0.7)

Flow @ 60 Cycles gpm (L/min) 23.5 (88.8)

Noise Level @ 60 psi dBA 86.8

Weight* lb (kg)

96 (43.5)

Container Suitability

Remote Mounting


Dimensions

A 1 in (mm) 48.73 (1237.72)

B in (mm) 25.67 (652.12)

C in (mm) 19.54 (496.32)

PERFORMANCE BASED ON 30wt. OIL (100 cSt) AT 40° C TEMPERATURE CYCLES PER MINUTE (CPM)




FLOW RATE - GALLONS PER MINUTE (GPM)

NOTE: NON SHADED AREA OF THE GRAPH REPRESENTS RECOMMENDED OPERATING RANGE

PERFORMANCE BASED ON 30wt. OIL (100 cSt) AT 40° C TEMPERATURE

CYCLES PER MINUTE (CPM)



FLOW RATE - LITERS PER MINUTE (LPM)

NOTE: NON SHADED AREA OF THE GRAPH REPRESENTS RECOMMENDED OPERATING RANGE