

SPECIFICATION

AF0828S Series Chop Check Piston Pump

Ratio	28:1
-------	------

Stroke 6" (15.24 cm)

Material Inlet Flange Mount

Material Outlet 1-1/4" NPT(F)

Air Inlet (female) 1/2" NPT(F)

Air Inlet Pressure Range psi (bar) 30 - 120 (2.1 - 8.3)

Fluid Pressure Range psi (bar) 840 - 3360 (57.9 - 231.7)

Max Cycles/Minute 70

Displacement/Cycle cu in (cm3) 20.0 (327.8)

Cycles/gal (L) 11.55 (3.0)

Flow @ **70** Cycles gpm (L/min) 6.0 (22.7)

Noise Level @ 60 psi dBA 86.8


Weight* lb (kg) 140 (63.5)

A 1 in (mm) 53.46 (1357.88)


B in (mm) 30.41 (772.29)

C in (mm) 19.25 (488.95)

PERFORMANCE BASED ON 30wt OIL (100cSt) AT 40° C TEMPERATURE



NOTE: NON SHADED AREA OF THE GRAPH REPRESENTS RECOMMENDED OPERATING RANGE



NOTE: NON SHADED AREA OF THE GRAPH REPRESENTS RECOMMENDED OPERATING RANGE