

GD Series - Submersible Portable Dewatering Pumps

Item		Description
Limits of Use	Liquid Temp.	0~40° C(32~104° F)
	Applications	Construction sites、 Basins dewatering
Type	Frequency	50Hz/60Hz
	Motor	2P (50Hz 3000rpm · 60Hz 3600rpm) · Dry Motor
	Insulation	Class B (GD-400(R)/750(R)) · Class F (GD-1100)
	Protection	IP68
	Protector	Auto-cut
	Bearing	Ball type
	M.seal	Double M.seals
	Impeller	Vortex
Material	Upper Cover	ADC12/383 (GD-400(R)/750(R)) · FC200/GG-20 (GD-1100)
	Motor Frame	ADC12/383 (GD-400(R)/750(R)) · FC200/GG-20 (GD-1100)
	Shaft	SUS410/X10Cr13 (GD-400(R)/750(R)) · SUS403/X5Cr13 (GD-1100)
	M.seal	CA/CE & SiC/SiC
	Casing	Synthetic Rubber (GD-400(R)/750(R)) · FCD500/GGG-50 (GD-1100)
	Impeller	Urethane Rubber + SPCC (GD-400(R)/750(R)) ·

Item		Description
		Chrome Steel (GD-1100)
	Strainer	SUS304/X5CrNi18-10
	Cable	VCT or H07RN-F or SJOW
Optional		Pumps can be customized to fit specifications