

GF Series - Submersible Grinder Pumps

50Hz

Item		Description
Limits of Use	Liquid Temp.	0~40°C (32~104°F)
	Applications	Residential Wastewater • Sewage
Type	Frequency	50Hz
	Motor	2P (3000rpm) • Dry Motor
	Insulation	Class F (1.3HP~5HP) • Class H (7.5~10HP)
	Protection	IP68
	Protector	Auto-cut
	Bearing	Ball type
	M.seal	Double M.seals
	Impeller	Vortex
Material	Upper Cover	FC200
	Motor Frame	FC200
	Shaft	SUS403
	M.seal	CA/CE & SiC/SiC
	Casing	FC200
	Impeller	FC200
	Radial Cutter	SUS440C
	Cutter Ring	SUS440C
	Cable	VCT or H07RN-F or SJOW/SOW
Optional		Pumps can be customized to fit specifications DN40 CasingFloating Switch (32GF21.0/21.5/21.5H/22.2)

60Hz

Item		Description
Limits of Use	Liquid Temp.	0~40°C (32~104°F)
	Applications	Residential Wastewater • Sewage
Type	Frequency	60Hz
	Motor	2P (3600rpm) • Dry Motor
	Insulation	Class F (1.3HP~5HP) • Class H (7.5~10HP)
	Protection	IP68
	Protector	Auto-cut
	Bearing	Ball type
	M.seal	Double M.seals
	Impeller	Vortex
Material	Upper Cover	FC200
	Motor Frame	FC200
	Shaft	SUS403
	M.seal	CA/CE & SiC/SiC
	Casing	FC200
	Impeller	FC200
	Radial Cutter	SUS440C
	Cutter Ring	SUS440C
	Cable	VCT or H07RN-F or SJOW/SOW
Optional		Pumps can be customized to fit specifications DN40 CasingFloating Switch (32GF21.0/21.5/21.5H/22.2/22.2H)