### **Product Data**



# **Room Thermostat**

For two-pipe applications heating or cooling, with fan control



The room thermostat is used for individual temperature control of two-pipe systems. The room temperature is controlled via a valve which is controlled by the room thermostat via a thermal actuator. When the room temperature reaches the setpoint temperature, the valve is closed. In addition, the room thermostat enables the electrical control of fan coil units for demand-oriented heating or cooling.

The fan speed can be controlled automatically or manually in three stages.

#### **Features**

- + Intuitive operation
- + Energy-saving room temperature control
- + LC display with backlight


# **Product Details**

#### Room thermostat with fan control

The room temperature is set using the arrow keys on the room thermostat. The fan speed can be set automatically or manually in three stages. Your settings are permanently saved. Even after a power failure, the configuration is retained.

#### **Functions**

- Temperature setting accurate to the degree
- Selection of various time profiles
- Manual selection of individual modes (heating, cooling, fan) independently of the time profile
- Fan speed control
- Adjustable sleep mode



Technical Data		
Item no.	1152453	
Temperature range	535 °C	
Control	On/off	
Fuse	Without	
Switching current (short-time)	Resistive load 3A Inductive load 2A	
Mounting	Flush	
Protection class	IP 21	
Colour	White	
Power consumption	- <2 W	
Operating voltage	100240 V AC 50/60 Hz	
Switching temperature difference	± 1 K	
Dimensions	88 mm x 88 mm x 45 mm	

N	Neutral conductor
L	Phase
(1)	Fan stage 1 (LOW)
(2)	Fan stage 2 (MED)
(3)	Fan stage 3 (HIGH)
(4)	Valve control (open/closed)

## Accessories

#### Aktor T 2P thermal actuator

On/off control, threaded connection M 30  $\times$  1.5.

Suitable for	Item no.
<ul> <li>Room thermostat</li> <li>FloorCon F electrical connecting block</li> <li>Electrical connecting blocks</li> </ul>	1012415 (230 V NC) 1012425 (230 V NO)

Subject to changes • All rights reserved • © 2023 Oventrop GmbH & Co. KG EN-12102-1152453-DB-V2334 – August 2023

