

Coming Soon to the US Market

Vitocal Ductless and Ducted Heat Pumps

Viessmann is proud to provide an early view of the upcoming Vitocal Ductless and Ducted air to air heat pump solutions for the US market. This new offering utilizes the next generation R454B refrigerant which has no Ozone depletion potential (ODP) and 75% lower Global Warming potential (GWP) compared to R-410A. Vitocal Ductless and Ducted Heat Pumps deliver ultra-quiet and efficient comfort, year round for any space and style.

VITOCAL 100-S

Ductless single zone



- ★ High Efficiency Inverter Up to 27.5 SEER2 , 18 EER2, 14.8 HSPF2
- ★ Sizes: 06 / 09 / 12 / 18 / 24 / 30 / 33/ 36 / 48 / 58
- ★ 100% heating capacity at 5° F (-15° C)
- ★ Extremely quiet outdoor operation, as low as 53 dB(A)1
- ★ Matched Indoor Unit Selection - air handlers, 1-way cassettes, 4-way cassettes, floor consoles, ceiling and floor consoles, slim ducted units (low and high static) and high walls
- ★ Cooling operating range -22° ~ 122° F (-30° ~ 50° C)
- ★ Heating operating range -22° ~ 86° F (-30° ~ 30° C)
- ★ Anti-corrosive fin coating
- ★ Built-in basepan heater
- ★ Refrigerant leakage detection

VITOCAL 100-S

Ducted single zone



- ★ High Efficiency Inverter Up to 18.8 SEER2 , 11 EER2, 9.7 HSPF2
- ★ Sizes: 18 / 24 / 30 / 36 / 48 / 60
- ★ Best of Both Worlds- Traditional ductwork and standard 3/8" + 3/4" linesets with the performance boost of compact inverter technology. Great for retrofits or new construction.
- ★ Integrated 24V and RS-485 communication
- ★ Up to 100% heating capacity at 5° F
- ★ Extremely quiet outdoor operation, as low as 55 dB(A)1
- ★ Cooling operating range -22° ~ 122° F (-30° ~ 50° C)
- ★ Heating operating range -22° ~ 75° F (-30° ~ 24° C)
- ★ Built-in basepan heater
- ★ Anti-corrosive fin coating
- ★ Refrigerant leakage detection

VITOCAL 200-S

Ductless multi zone



- ★ High Efficiency Inverter Up to 25 SEER2 , 15 EER2, 11.8 HSPF2
- ★ Sizes: 18 / 24 / 30 / 36 / 48 / 60
- ★ Multi Zone- Pair from 2 up to 6 Indoor units per Multi Zone System
- ★ Up to 116% heating capacity at 5° F
- ★ Extremely quiet outdoor operation, as low as 61 dB(A)1
- ★ Indoor Unit Selection - air handlers, 1-way cassettes, 4-way cassettes, floor consoles, ceiling and floor consoles, slim ducted units (low and high static) and high walls
- ★ Cooling operating range -22° ~ 122° F (-30° ~ 50° C)
- ★ Heating operating range -22° ~ 75° F (-30° ~ 24° C)
- ★ Anti-corrosive fin coating
- ★ Built-in basepan heater
- ★ Refrigerant leakage detection

